



Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Revision Date: 07/29/2026

Date of Issue: 06/02/2020

Supersedes Date: 06/02/2020

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Aluminum, 3xxx Series Alloys

1.2 Recommended Use and Restrictions on Use

Use Of The Substance/Mixture : Fabricated Parts

Restrictions On Use : No additional information available

1.3. Name, Address, and Telephone of the Responsible Party

Company

TCI – Texarkana, Inc

300 Alumax Drive

Nash, TX 75569

T 1-903-832-8471

Email:

EHS@texarkanaaluminum.com

Website: www.texarkanaaluminum.com

1.4. Emergency Telephone Number

Emergency Number : VelocityEHS
(800)255-3924 (North America)
+1 (813)248-0585 (International)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Hazardous to the aquatic environment — Acute Hazard, Category 3 H402

Combustible dust

2.2. Label Elements

GHS-US Labeling

Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) : CODU - May form combustible dust concentrations in air if small particles are generated during further processing, handling or by other means.
H402 - Harmful to aquatic life.

Precautionary Statements (GHS-US) : P273 - Avoid release to the environment.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

Supplemental Information : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Proper grounding procedures to avoid static electricity should be followed. Prevent dust accumulation (to minimize explosion hazard). Avoid generating dust.

2.3 Hazards associated with known or reasonably anticipated uses

If this product is used in unforeseeable chemical processes and not used as intended or reasonable, the hazards listed in Section 2.3 cannot cover all chemistries. Therefore, a Process Hazard Analysis (PHA) or other hazard assessment for additional specific end uses should be performed to ensure that hazards are fully understood, and adequate safety measures are in place. See Section 10 for relevant reactivity and stability information. *Hazards from expected use:* This product may produce gases and fumes including metal fumes, ozone, nitrogen dioxide, and nitrogen monoxide during welding or smelting operations. The following hazards may be observed: H314 / H315 - Causes skin burns and eye irritation or irritation; H318 / H319 - Causes serious eye damage or irritation; H330 / H331 / H332 – Fatal, Toxic, or harmful if inhaled; H370 - Causes damage to organs if inhaled; H372 - Causes damage to organs through prolonged or repeated exposure if inhaled. The severities of the individual symptoms are dependent upon the level of exposure(s). Inhalation of dusts and fumes can cause metal fume fever.

2.4. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Risk of thermal burns on contact with molten product.

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

2.5. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

Name	Synonyms	Product Identifier	%*	GHS US classification
Aluminum	Aluminium / Aluminium metal / Aluminium, metal / Aluminum metal / Aluminum, elemental / Aluminum, metal / C.I. 77000 / CI 77000 / Aluminium powder (stabilised) / Aluminium powder (stabilized) / Aluminium powder / Pigment Metal 1 / Aluminum powder / Aluminium metal, powder / Aluminium powder (pyrophoric)	(CAS-No.) 7429-90-5	96 - 100	Combustible Dust
Manganese	Manganese, elemental / Manganese metal	(CAS-No.) 7439-96-5	1 - 1.5	Combustible Dust
Distillates, petroleum, hydrotreated middle	Petroleum distillates, hydrotreated middle / Distillates (petroleum), hydrotreated middle / Distillates, hydrotreated middle petroleum / Distillates (petroleum) hydrotreated middle / Distillates, (petroleum), hydrotreated middle / Hydrotreated middle distillate (petroleum) / Distillates (petroleum), hydrotreated middle- gas oil - unspecified / (Petroleum) distillates, hydrotreated middle / Isopar V / C13-15 ALKANE / Paraffin oil / Paraffin - C15-19 alkane / Distillates, petroleum, hydrotreated middle (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11-25 and boiling in the range of approximately 205-400°C.) / Petroleum distillate, hydrogenated, middle / Distillates(petroleum), hydrotreated middle / Distillates (petroleum), hydrotreated middle; Gasoil - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately; 205°C to 400°C (401°F to 752°F).]	(CAS-No.) 64742-46-7	0.1 - 1	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 3, H402 Aquatic Chronic 2, H411
Iron	Iron, elemental / Direct reduced Iron / Iron, reduced / Elemental iron / IRON POWDER	(CAS-No.) 7439-89-6	<= 0.7	Combustible Dust
Silicon	Silicon powder / Silicon powder, amorphous / Ammonium hexafluorosilicate	(CAS-No.) 7440-21-3	<= 0.6	Combustible Dust

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Copper	C.I. 77400 / C.I. Pigment Metal 2 / Copper, elemental / CI 77400 / Copper metal / Copper, metallic / Pigment Metal 2 / Granulated copper	(CAS-No.) 7440-50-8	0.05 - 0.2	Combustible Dust
Zinc	C.I. Pigment Black 16 / C.I. Pigment Metal 6 / Zinc (metallic) / Pigment Black 16 / Zinc powder - zinc dust (stabilised) / Zinc powder - zinc dust (pyrophoric)	(CAS-No.) 7440-66-6	0.1	Combustible Dust
The ingredients listed below are compounds which could be formed during further processing operations.				
Name	Synonyms	Product Identifier	%	GHS US classification
Aluminum compounds	Aluminium compounds / Aluminium compounds, all unspecified	(CAS-No.) Not applicable	Not applicable	Not classified
Iron compounds	Iron compounds, all unspecified	(CAS-No.) Not applicable	Not applicable	Not classified
Copper compounds	Copper based compounds	(CAS-No.) Not applicable	Not applicable	Not classified
Copper, inorganic compounds	Copper inorganic compounds / Copper compounds, inorganic / Copper inorganic compounds, all unspecified	(CAS-No.) Not applicable	Not applicable	Not classified
Alloys of copper	Copper alloys	(CAS-No.) Not Applicable	Not applicable	Not classified
Manganese compounds	Manganese compounds, n.o.s.	(CAS-No.) Not applicable	Not applicable	Not classified
Manganese inorganic compounds	Manganese compounds, inorganic / Manganese, inorganic compounds	(CAS-No.) Not applicable	Not applicable	Not classified
Zinc compounds	Zinc compounds, n.o.s.	(CAS-No.) Not applicable	Not applicable	Not classified
Zinc powder - zinc dust (stabilised)	Zinc powder- zinc dust (stabilized) / Zinc dust / Zinc powder / Zinc powder - zinc dust (stabilized) / Zinc powder-zinc dust (stabilised) / Zinc powder-zinc dust, stabilised	(CAS-No.) Not Applicable	Not applicable	Not classified
Zinc, inorganic compounds	Zinc inorganic compounds	(CAS-No.) Not Applicable	Not applicable	Not classified
Silica, amorphous, precipitated and gel	Precipitated silica / Silica gel / Silica gel, precipitated, crystalline free / Silica, amorphous, gel / Silica gel, precipitated, crystalline-free / Silica gel, crystalline free / Precipitated silica and silica gel / Silica gel, crystalline-free / Hydrated silica / Amorphous silicon dioxide / Synthetic amorphous silicon dioxide / Silica gel, precipitated / Dioxosilane / Silica, amorphous and synthetic, precipitated and gel	(CAS-No.) 112926-00-8	Not applicable	Not classified
Nitrogen monoxide	Nitric oxide / Nitrogen oxide (NO) / Nitric monoxide / Nitric oxide, compressed / Nitrogen(II) oxide	(CAS-No.) 10102-43-9	Not applicable	Ox. Gas 1, H270 Press. Gas (Comp.), H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 2, H373

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Ozone	Triatomic oxygen	(CAS-No.) 10028-15-6	Not applicable	Ox. Gas 1, H270 Acute Tox. 1 (Inhalation:gas), H330 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Aluminum oxide (Al2O3)	Aluminum oxide / .alpha.- Alumina / Alumina / Aluminium oxide / Aluminium oxide (Al2O3) / .alpha.-Aluminum oxide / Alundum / ALUMINA / Dialuminium trioxide / Dialuminum trioxide	(CAS-No.) 1344-28-1	Not applicable	Not classified
Zinc oxide (ZnO)	Zinc oxide / C.I. 77947 / C.I. Pigment White 4 / Zinc White / CI 77947 / Pigment White 4	(CAS-No.) 1314-13-2	Not applicable	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Iron oxide (Fe2O3)	C.I. 77491 / C.I. Pigment Red 101 / Diiron trioxide / Ferric oxide / Iron sesquioxide / Iron(III) oxide / Red Iron Oxide / Rouge / CI 77491 / Iron trioxide / Sienna / Pigment Red 101 / Red iron oxide / Red iron oxide pigment / Iron Oxide Red / Diiron(III) trioxide / Iron oxide	(CAS-No.) 1309-37-1	Not applicable	Combustible Dust
Nitrogen dioxide	Nitrogen oxide (NO2) / Nitrogen oxide / Nitrogen(IV) oxide / Nitrogen peroxide	(CAS-No.) 10102-44-0	Not applicable	Ox. Gas 1, H270 Press. Gas (Comp.), H280 Acute Tox. 1 (Inhalation:gas), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318
Magnesium oxide (MgO)	Calcined magnesite / Magnesium oxide / MAGNESIUM OXIDE / Magnesia	(CAS-No.) 1309-48-4	Not applicable	Not classified

* The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the 29 CFR 1910.1200. Percentages are listed in weight-by-weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume-by-volume percentage (v/v%). Full text of H-phrases: see section 16. *This mixture has a variable composition.*

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: Using proper respiratory protection, move the exposed person to fresh air at once. Encourage exposed person to cough, spit out, and blow nose to remove dust. Immediately call a poison center, physician, or emergency medical service.

First-aid Measures After Skin Contact: For particulates and dust: Brush off loose particles from skin. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. *In molten form:* Drench affected area with water for at least 15 minutes. Get immediate medical advice/attention. Removal of solidified molten material from skin requires medical assistance.

First-aid Measures After Eye Contact: For particulates and dust: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention. *In molten form:* Immediately rinse with water for at least 15 minutes. Get immediate medical advice/attention. Removal of solidified molten material from the eyes requires medical assistance.

First-aid Measures After Ingestion: Not expected to be a primary route of exposure. Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: This product is not hazardous in the form in which it is shipped by the manufacturer. Risk of thermal burns on contact with molten product. Welding, cutting, or processing this material may release dust or fumes that are hazardous. Contact may cause irritation due to mechanical abrasion.

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Symptoms/Injuries After Inhalation: Dust may be harmful or cause irritation. Fumes from welding, or processing of this material can be harmful if inhaled. Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation. Skin contact with large amounts of dust may cause mechanical irritation. Risk of thermal burns on contact with molten product.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes. May cause mechanical eye irritation. Risk of thermal burns on contact with molten product.

Symptoms/Injuries After Ingestion: Not expected to be a primary route of exposure. Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: In massive form, no chronic hazard exists. If physically altered to present slivers, ribbons, dusts or fumes from molten material: Prolonged exposure to welding fume is associated with causing lung damage, stomach ulcers, kidney damage, nervous system damage and various types of cancer, including lung, larynx and urinary tract. Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. If heated to the point of fume generation zinc fumes may cause metal fume fever. Otherwise, zinc is non-toxic. Manganese: Chronic exposure can cause inflammation of the lung tissue, scarring the lungs (pulmonary fibrosis). Chronic exposure to excessive manganese levels can lead to a variety of psychiatric and motor disturbances, termed manganism. Silicon: Can cause chronic bronchitis and narrowing of the airways. Repeated inhalation of iron oxide dust can cause siderosis a benign condition.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand. Fluorescein may be of use as a diagnostic aid to determine the extent of mechanical irritation/damage in cases of eye exposure.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: For metal fires, dry sand or graphite may be used. Class D fire extinguishers are also appropriate.

Unsuitable Extinguishing Media: If material is hot or in dust form, do not use a heavy water stream. DO NOT USE: Halogenated agents on small chips, dusts or fines.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: In massive form: Product is not flammable. The following applies to the product if it is cut, sanded or altered in such a way that excessive and/or significant particulates and/or dusts may be generated: Flammable solid. Reacts readily with water to produce flammable gases which may ignite and cause a fire. Combustible Dust.

Explosion Hazard: In massive form: Product is not explosive. For particulates and dust: Reacts readily with water to emit flammable gases which could ignite and possibly cause an explosion. Dust explosion hazard in air.

Reactivity: May form explosive hydrogen gas on contact with acids. In molten form may react violently with water. For particulates and dust: Reacts readily with water liberating highly flammable gases. Reacts violently with strong oxidizers. Increased risk of fire or explosion. May react violently with halogens or halogenated compounds. Contact with certain metal oxides may result in a thermite reaction with a source of ignition.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not disturb burning metal. Dust, fines, or molten metal: Use Class D extinguishing agents. As shipped: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical. Use extinguishing media appropriate for surrounding fire.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Metal oxides.

Other Information: Fine dust dispersed in air may ignite. Do not allow run-off from firefighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid generating dust. For particulates and dust: Remove ignition sources. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use only non-sparking tools.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Emergency Procedures: Ventilate area. Eliminate ignition sources. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. Use only non-sparking tools. Avoid generation of dust during clean-up of spills.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. As shipped: Mechanically recover the product. For particulates and dust: Vacuum clean-up is preferred. If sweeping is required use water mist as a dust suppressant. Use explosion proof vacuum during cleanup, with appropriate filter. Do not mix with other materials. Use only non-sparking tools. Spills should be cleaned up immediately and placed in approved containers. For small molten spills, allow product to cool and remove as a solid. Use cautious judgement when cleaning up large molten spills. Wear personal protective equipment as appropriate, shut off source of leak if safe to do so, dike and contain molten material, and collect in approved containers for disposal in accordance with federal, state, and local regulations. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: This product is physiologically inert in its massive form. However, user-generated dust and/or fumes may pose a physiological hazard if inhaled or ingested. Avoid inhalation of metal dusts and fumes. May cause an influenza-like illness. Avoid skin and eye contact with dusts to prevent mechanical irritation. User-generated dust is easily ignited and difficult to extinguish. Avoid dust production. Keep away from any possible contact with water, because of violent reaction and possible flash fire. Accumulation and dispersion of dust with an ignition source can cause a combustible dust explosion. Keep dust levels to a minimum and follow applicable regulations. Fumes from welding, or processing of this material can be harmful if inhaled. Hexavalent chrome may be formed during welding. The welding of alloys may generate carbon monoxide, carbon dioxide, ozone, nitrogen oxides, infrared radiation, and ultra-violet radiation. Do not dry clean dust covered objects and floors. Vacuum, wipe or sweep up the majority of the product, then use copious quantities of water and cleaning solution when rinsing off remainder.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not breathe dust. Avoid contact with eyes, skin and clothing. Protect from moisture. Keep away from heat, sparks, open flames, hot surfaces. – No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid creating or spreading dust. Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

Handling Temperature: No temperature range given. Product may be used in molten form.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash contaminated clothing before reuse.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Avoid creating or spreading dust. Take action to prevent static discharges. Proper grounding procedures to avoid static electricity should be followed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry place. Keep/Store away from incompatible materials. For particulates and dust: Store in a well-ventilated place. Keep container tightly closed. Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep in fireproof place.

Incompatible Materials: Corrosive substances in contact with metals may produce flammable hydrogen gas. Chips, fines, dust and molten metal are considerably more reactive with the following: Strong oxidizers: Violent reaction with considerable heat generation. Can react explosively with nitrates (e.g., ammonium nitrate and fertilizers containing nitrate) when heated or molten. Acids and alkalis: Reacts to generate flammable/explosive hydrogen gas. Generation rate is greatly increased with smaller particles (e.g., fines and dusts). Halogenated compounds: Many halogenated hydrocarbons, including halogenated fire extinguishing agents, can react violently with finely divided or molten metal. Iron oxide (rust) and other metal oxides (e.g., copper and lead oxides): A violent thermite reaction generating considerable heat can occur. Reaction with aluminum fines and dusts requires only very weak ignition sources for initiation. Molten aluminum can react violently with iron oxide without external ignition source. Iron powder and water: Explosive reaction forming hydrogen gas when heated above 1470°F (800°C). Thermite explosions have been reported when aluminum alloys were melted in furnaces used for alloying with lead, bismuth or other metals with low melting temperatures. These metals, when added as high purity ingots, can seep through cracks in furnace liners and become oxidized. During subsequent melts in the furnace, molten aluminum can contact these metal oxides resulting in a thermite explosion. *Thermite reactions can occur with oxides of lead, copper, iron, bismuth and certain other metals.*

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Storage Temperature: No temperature range given. Product may be used in molten form.
Storage Area: Store in ventilated dry area, away from sources of water or combustible materials. Refer to local codes and regulations.

7.3. Specific End Use(s)

Fabricated Parts

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Aluminum (7429-90-5)		
USA ACGIH	ACGIH® TLV® TWA	1 mg/m³ (respirable particulate matter)
USA ACGIH	ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL TWA	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)
USA OSHA	OSHA PEL TWA	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)
Silicon (7440-21-3)		
USA NIOSH	NIOSH REL TWA	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)
USA OSHA	OSHA PEL TWA	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)
Copper (7440-50-8)		
USA ACGIH	ACGIH® TLV® TWA	0.2 mg/m³ (fume)
USA NIOSH	NIOSH REL TWA	1 mg/m³ (dust and mist) 0.1 mg/m³ (fume)
USA IDLH	IDLH	100 mg/m³ (dust, fume and mist)
USA OSHA	OSHA PEL TWA	0.1 mg/m³ (fume) 1 mg/m³ (dust and mist)
Manganese (7439-96-5)		
USA ACGIH	ACGIH® TLV® TWA	0.02 mg/m³ (respirable particulate matter) 0.1 mg/m³ (inhalable particulate matter)
USA ACGIH	ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL TWA	1 mg/m³ (fume)
USA NIOSH	NIOSH REL STEL	3 mg/m³
USA IDLH	IDLH	500 mg/m³
USA OSHA	OSHA PEL C	5 mg/m³ (fume)
Aluminum, welding fumes		
USA NIOSH	NIOSH REL TWA	5 mg/m³
Copper compounds		
USA ACGIH	ACGIH® TLV® TWA	1 mg/m³ (dust and mist)
USA NIOSH	NIOSH REL TWA	1 mg/m³ (dust and mist)
USA IDLH	IDLH	100 mg/m³ (dust and mist)
Manganese compounds		
USA NIOSH	NIOSH REL TWA	1 mg/m³
USA NIOSH	NIOSH REL STEL	3 mg/m³
USA IDLH	IDLH	500 mg/m³
USA OSHA	OSHA PEL C	5 mg/m³
Manganese inorganic compounds		
USA ACGIH	ACGIH® TLV® TWA	0.02 mg/m³ (respirable particulate matter) 0.1 mg/m³ (inhalable particulate matter)
USA ACGIH	ACGIH® chemical category	Not Classifiable as a Human Carcinogen
Silica, amorphous, precipitated and gel (112926-00-8)		
USA OSHA	OSHA PEL TWA	20 mppcf

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

USA OSHA	OSHA PEL TWA	20 mppcf, 80/(SiO ₂) mg/m ³ (See 29 CFR 1910.1000 TABLE Z-3)
Nitrogen monoxide (10102-43-9)		
USA ACGIH	ACGIH® TLV® TWA	25 ppm
USA ACGIH	BEI	5 % of hemoglobin Parameter: Methemoglobin - Medium: blood - Sampling time: during or end of shift (background, nonspecific, semi-quantitative)
USA NIOSH	NIOSH REL TWA	30 mg/m ³
USA NIOSH	NIOSH REL TWA	25 ppm
USA IDLH	IDLH	100 ppm
USA OSHA	OSHA PEL TWA	30 mg/m ³
USA OSHA	OSHA PEL TWA	25 ppm
Ozone (10028-15-6)		
USA ACGIH	ACGIH® TLV® TWA	0.05 ppm (heavy work) 0.08 ppm (moderate work) 0.1 ppm (light work) 0.2 ppm (heavy, moderate or light workloads, <=2 hours)
USA ACGIH	ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL C	0.2 mg/m ³
USA NIOSH	NIOSH REL C	0.1 ppm
USA IDLH	IDLH	5 ppm
USA OSHA	OSHA PEL TWA	0.2 mg/m ³
USA OSHA	OSHA PEL TWA	0.1 ppm
Aluminum oxide (Al₂O₃) (1344-28-1)		
USA ACGIH	ACGIH® TLV® TWA	10 mg/m ³
USA OSHA	OSHA PEL TWA	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Zinc oxide (ZnO) (1314-13-2)		
USA ACGIH	ACGIH® TLV® TWA	2 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH® TLV® STEL	10 mg/m ³ (respirable particulate matter)
USA NIOSH	NIOSH REL TWA	5 mg/m ³ (dust and fume)
USA NIOSH	NIOSH REL STEL	10 mg/m ³ (fume)
USA NIOSH	NIOSH REL C	15 mg/m ³ (dust)
USA IDLH	IDLH	500 mg/m ³
USA OSHA	OSHA PEL TWA	5 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Iron oxide (Fe₂O₃) (1309-37-1)		
USA ACGIH	ACGIH® TLV® TWA	5 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL TWA	5 mg/m ³ (dust and fume)
USA IDLH	IDLH	2500 mg/m ³ (dust and fume)
USA OSHA	OSHA PEL TWA	10 mg/m ³ (fume) 15 mg/m ³ (total dust (Rouge)) 5 mg/m ³ (respirable fraction (Rouge))
Nitrogen dioxide (10102-44-0)		
USA ACGIH	ACGIH® TLV® TWA	0.2 ppm
USA ACGIH	ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL STEL	1.8 mg/m ³
USA NIOSH	NIOSH REL STEL	1 ppm
USA IDLH	IDLH	13 ppm
USA OSHA	OSHA PEL C	9 mg/m ³
USA OSHA	OSHA PEL C	5 ppm

Aluminum, 3xxx Series Alloys

Safety Data Sheet
According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Magnesium oxide (MgO) (1309-48-4)		
USA ACGIH	ACGIH® TLV® TWA	10 mg/m³ (inhalable particulate matter)
USA ACGIH	ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA IDLH	IDLH	750 mg/m³ (fume)
USA OSHA	OSHA PEL TWA	15 mg/m³ (fume, total particulate)

8.2. Exposure Controls

Appropriate Engineering Controls	: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure all national/local regulations are observed. Although not all inclusive, see ANSI Z49.1:2012 Safety in Welding, Cutting, and Allied Processing for welding specific engineering controls.
Personal Protective Equipment	: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.
	
Materials for Protective Clothing	: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.
Hand Protection	: Wear protective gloves.
Eye and Face Protection	: Chemical safety goggles. Faceshield as determined by task.
Skin and Body Protection	: Wear suitable protective clothing. Reference ANSI Z49.1:2012 for PPE guidance for welders.
Respiratory Protection	: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.
Thermal Hazard Protection	: If material is hot, wear thermally resistant protective gloves.
Environmental Exposure Controls	: Avoid release to the environment.
Other Information	: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Color	: Spherical aluminum solid, silver
Odor	: None
pH	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Flammable solid
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity, Kinematic	: No data available

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Particle Size	: No data available
Particle Size Distribution	: No data available
Particle Shape	: No data available
Particle Aspect Ratio	: No data available
Particle Aggregation State	: No data available
Particle Agglomeration State	: No data available
Particle Specific Surface Area	: No data available
Particle Dustiness	: No data available

9.2. Other Information

No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

May form explosive hydrogen gas on contact with acids. In molten form may react violently with water. For particulates and dust: Reacts readily with water liberating highly flammable gases. Reacts violently with strong oxidizers. Increased risk of fire or explosion. May react violently with halogens or halogenated compounds. Contact with certain metal oxides may result in a thermite reaction with a source of ignition.

10.2. Chemical Stability

Stable under normal conditions. The following applies to the product if it is cut, sanded or altered in such a way that excessive and/or significant particulates and/or dusts may be generated: Flammable solid. Water reactive.

10.3. Possibility of Hazardous Reactions, Including those Associated with Foreseeable Emergencies

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Keep away from moisture, water, ignition sources, direct sunlight, extremely high or low temperatures, incompatible materials. Sparks, heat, open flame and other sources of ignition. Dust accumulation (to minimize explosion hazard).

10.5. Incompatible Materials

Corrosive substances in contact with metals may produce flammable hydrogen gas. Chips, fines, dust and molten metal are considerably more reactive with the following: Strong oxidizers: Violent reaction with considerable heat generation. Can react explosively with nitrates (e.g., ammonium nitrate and fertilizers containing nitrate) when heated or molten. Acids and alkalis: Reacts to generate flammable/explosive hydrogen gas. Generation rate is greatly increased with smaller particles (e.g., fines and dusts). Halogenated compounds: Many halogenated hydrocarbons, including halogenated fire extinguishing agents, can react violently with finely divided or molten metal. Iron oxide (rust) and other metal oxides (e.g., copper and lead oxides): A violent thermite reaction generating considerable heat can occur. Reaction with aluminum fines and dusts requires only very weak ignition sources for initiation. Molten aluminum can react violently with iron oxide without external ignition source. Iron powder and water: Explosive reaction forming hydrogen gas when heated above 1470°F (800°C). Thermite explosions have been reported when aluminum alloys were melted in furnaces used for alloying with lead, bismuth or other metals with low melting temperatures. These metals, when added as high purity ingots, can seep through cracks in furnace liners and become oxidized. During subsequent melts in the furnace, molten aluminum can contact these metal oxides resulting in a thermite explosion. *Thermite reactions can occur with oxides of lead, copper, iron, bismuth and certain other metals.*

10.6. Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Likely Routes of Exposure: Dermal, Eye Contact, Inhalation, Oral

Acute Toxicity (Oral): Not classified.

Acute Toxicity (Dermal): Not classified.

Acute Toxicity (Inhalation): Not classified.

Aluminum (7429-90-5)	
LC50 Inhalation Rat	0.888 mg/L/4h (No deaths)
Distillates, petroleum, hydrotreated middle (64742-46-7)	
LD50 Oral Rat	7400 mg/kg (Source: IUCLID)
LD50 Dermal Rabbit	> 2000 mg/kg (Source: ECHA_API)
LC50 Inhalation Rat	4.6 mg/l/4h
Silicon (7440-21-3)	
LD50 Oral Rat	3160 mg/kg
Iron (7439-89-6)	

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

LD50 Oral Rat	98.6 g/kg
---------------	-----------

Aluminum, 3xxx Series Alloys

Safety Data Sheet
According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Copper (7440-50-8)	
LC50 Inhalation Rat	> 5.11 mg/l/4h
Manganese (7439-96-5)	
LD50 Oral Rat	> 2000 mg/kg
LC50 Inhalation Rat	> 5.14 mg/l/4h
Zinc (7440-66-6)	
LD50 Oral Rat	> 2000 mg/kg
Silica, amorphous, precipitated and gel (112926-00-8)	
LD50 Oral Rat	> 20000 mg/kg (Source: ECHA)
Nitrogen monoxide (10102-43-9)	
LC50 Inhalation Rat	1068 mg/m³ (Exposure time: 4 h Source: NLM_CIP)
LC50 Inhalation Rat	354 ppm/4h
Ozone (10028-15-6)	
LC50 Inhalation Rat	4800 ppb (Exposure time: 4 h Source: NLM_CIP)
LC50 Inhalation Rat	4.8 ppm
ATE (Gases)	10.00 ppmV/4h
Aluminum oxide (Al2O3) (1344-28-1)	
LD50 Oral Rat	> 15900 mg/kg
Zinc oxide (ZnO) (1314-13-2)	
LD50 Oral Rat	> 5000 mg/kg (Source: EU_RAR)
LD50 Dermal Rat	> 2000 mg/kg (no deaths)
LC50 Inhalation Rat	> 5700 mg/m³ (Exposure time: 4 h Source: ECHA_API)
LC50 Inhalation Rat	5.7 mg/l/4h
Iron oxide (Fe2O3) (1309-37-1)	
LD50 Oral Rat	> 10000 mg/kg (Source: ECHA)
LC50 Inhalation Rat	5.05 mg/l/4h
Nitrogen dioxide (10102-44-0)	
LC50 Inhalation Rat	88 ppm/4h
Magnesium oxide (MgO) (1309-48-4)	
LD50 Oral Rat	3870 mg/kg (Source: NLM_HSDB)

Skin Corrosion/Irritation: Not classified.

Serious Eye Damage/Irritation: Not classified.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Carcinogenicity: Not classified.

Silica, amorphous, precipitated and gel (112926-00-8)	
IARC group	3
Iron oxide (Fe2O3) (1309-37-1)	
IARC group	3

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: Dust may be harmful or cause irritation. Fumes from welding, or processing of this material can be harmful if inhaled. Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation. Skin contact with large amounts of dust may cause mechanical irritation. Risk of thermal burns on contact with molten product.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes. May cause mechanical eye irritation. Risk of thermal burns on contact with molten product.

Symptoms/Injuries After Ingestion: Not expected to be a primary route of exposure. Ingestion is likely to be harmful or have adverse effects.

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Chronic Symptoms: In massive form, no chronic hazard exists. If physically altered to present slivers, ribbons, dusts or fumes from molten material: Prolonged exposure to welding fume is associated with causing lung damage, stomach ulcers, kidney damage, nervous system damage and various types of cancer, including lung, larynx and urinary tract. Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. If heated to the point of fume generation zinc fumes may cause metal fume fever. Otherwise, zinc is non-toxic. Manganese: Chronic exposure can cause inflammation of the lung tissue, scarring the lungs (pulmonary fibrosis). Chronic exposure to excessive manganese levels can lead to a variety of psychiatric and motor disturbances, termed manganism. Silicon: Can cause chronic bronchitis and narrowing of the airways. Repeated inhalation of iron oxide dust can cause siderosis a benign condition.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Distillates, petroleum, hydrotreated middle (64742-46-7)	
LC50 Fish 1	35 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: IUCLID)
LC50 Fish 2	10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Copper (7440-50-8)	
LC50 Fish 1	0.0068 – 0.0156 mg/l (Exposure time: 96 h - Species: Pimephales promelas Source: EPA)
EC50 - Crustacea [1]	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	< 0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
Manganese (7439-96-5)	
LC50 Fish 1	> 3.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: ECHA)
ErC50 (Algae)	4.5 mg/l
NOEC Chronic Fish	3.6 mg/l (Exposure time: 96h; Species: Oncorhynchus mykiss)
Zinc (7440-66-6)	
EC50 - Crustacea [1]	0.169 mg/l
Silica, amorphous, precipitated and gel (112926-00-8)	
LC50 Fish 1	10000 mg/l
Aluminum oxide (Al2O3) (1344-28-1)	
LC50 Fish 1	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
ErC50 (Algae)	> 100 mg/l
NOEC (Acute)	> 50 mg/l
Zinc oxide (ZnO) (1314-13-2)	
LC50 Fish 1	1.793 mg/l (Exposure time: 96 h - Species: Zebrafish)
EC50 - Crustacea [1]	0.154 mg/l (Desmodesmus subspicatus 48 h)
ErC50 (Algae)	3.35 mg/l (Desmodesmus subspicatus 72 h)
NOEC Chronic Fish	0.026 mg/l (Jordanella floridae)
NOEC Chronic Crustacea	0.04 mg/l (Daphnia magna 21 d semi-static reproduction)
Iron oxide (Fe2O3) (1309-37-1)	
LC50 Fish 1	100000 mg/l (Exposure time: 96 h - Species: Danio rerio [static] Source: ECHA)

12.2. Persistence and Degradability

Aluminum, 3xxx Series Alloys	
Persistence and Degradability	Inorganic product which cannot be eliminated from water by biological purification processes.
Copper (7440-50-8)	
Persistence and Degradability	Not readily biodegradable.

12.3. Bioaccumulative Potential

Aluminum, 3xxx Series Alloys	
Bioaccumulative Potential	Bioaccumulation of metals cannot be excluded.

12.4. Mobility in Soil

Aluminum, 3xxx Series Alloys	
Ecology - Soil	Adsorption to solid soil phase is not expected.

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

12.5. Other Adverse Effects

Other Adverse Effects : None known.
Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Treatment Methods: Material should be recycled if possible. Can be landfilled or incinerated, when in compliance with local regulations.

Sewage Disposal Recommendations: Do not dispose of waste into sewer. Do not empty into drains.

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Recycle the material as far as possible.

Ecology - Waste Materials: Avoid release to the environment. Harmful to aquatic life.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Aluminum, 3xxx Series Alloys	
SARA Section 311/312 Hazard Classes	Physical hazard - Combustible dust
Aluminum (7429-90-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (dust or fume only)
Distillates, petroleum, hydrotreated middle (64742-46-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Silicon (7440-21-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Iron (7439-89-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Copper (7440-50-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm
SARA Section 313 - Emission Reporting	1 %
Manganese (7439-96-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 %
Zinc (7440-66-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	454 kg no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm
SARA Section 313 - Emission Reporting	1 % (dust or fume only)
Copper compounds	

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (includes any unique chemical substance that contains Copper as part of that chemical's infrastructure except for CAS numbers 147-14-8, 1328-53-6, or 14302-13-7, or copper phthalocyanine compounds that are substituted with only Hydrogen and/or Bromine and/or Chlorine that meet the molecular structure specified within the regulation)
Manganese compounds	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (includes any unique chemical substance that contains Manganese as part of that chemical's infrastructure)
Zinc compounds	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (includes any unique chemical substance that contains Zinc as part of that chemical's infrastructure)
Nitrogen monoxide (10102-43-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Listed on the United States SARA Section 302	
CERCLA RQ	10 lb releases to the air in amounts <1000 pounds per 24 hours which are the result of combustion and combustion-related activities are exempt from the notification requirements per 40 CFR 302.6
SARA Section 302 Threshold Planning Quantity (TPQ)	100 lb
Ozone (10028-15-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	100 lb
SARA Section 313 - Emission Reporting	1 %
Aluminum oxide (Al₂O₃) (1344-28-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (fibrous forms)
Zinc oxide (ZnO) (1314-13-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Iron oxide (Fe₂O₃) (1309-37-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Nitrogen dioxide (10102-44-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Listed on the United States SARA Section 302	
CERCLA RQ	10 lb releases to the air in amounts <1000 pounds per 24 hours which are the result of combustion and combustion-related activities are exempt from the notification requirements per 40 CFR 302.6
SARA Section 302 Threshold Planning Quantity (TPQ)	100 lb
Magnesium oxide (MgO) (1309-48-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	

15.2. US State Regulations

Aluminum (7429-90-5)
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Silicon (7440-21-3)

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Copper (7440-50-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Manganese (7439-96-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Zinc (7440-66-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Aluminum, welding fumes

U.S. - Pennsylvania - RTK (Right to Know) List

Copper compounds

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Manganese compounds

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Zinc compounds

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Silica, amorphous, precipitated and gel (112926-00-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Nitrogen monoxide (10102-43-9)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Ozone (10028-15-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Aluminum oxide (Al₂O₃) (1344-28-1)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Zinc oxide (ZnO) (1314-13-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Iron oxide (Fe2O3) (1309-37-1)
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
Nitrogen dioxide (10102-44-0)
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Magnesium oxide (MgO) (1309-48-4)
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision	: 07/29/2026
Indication of Changes	: Update of SDS to latest OSHA regulations under 29CFR1910.1200.
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H330	Fatal if inhaled
H332	Harmful if inhaled
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
SIAS	May displace oxygen and cause rapid suffocation

Glossary of Data Source Abbreviations

ATSDR: Agency for Toxic Substances and Disease Registry (U.S. Department of Health and Human Services)	FOOD_JOURN: Food Research Journal (1956)
AU_WES: Australia WES	IARC: The International Agency for Research on Cancer
CHEMVIEW: ChemView (U.S. Environmental Protection Agency)	IDLH: National Institute for Occupational Health and Safety Immediately Dangerous to Life or Health Value Profiles
EC_RAR: European Commission Renewal Assessment Report	IUCLID: International Uniform Chemical Information Database
EC_SCOEL: European Commission Scientific Committee on Occupational Exposure Limits	JAPAN_GHS: Japan GHS Basis for Classification Data
ECETOC: European Centre for Ecotoxicology and Toxicology of Chemicals Reports	JP_J-CHECK: Japan J-Check
ECHA_API: European Chemicals Agency API	KR_NIER: South Korea National Institute of Environmental Research Evaluations
ECHA_RAC: ECHA Committee for Risk Assessment	NICNAS: Australia National Industrial Chemicals Notification and Assessment Scheme
EFSA: European Food Safety Authority	NIOSH: National Institute for Occupational Health and Safety (U.S. Department of Health and Human Services)
EPA: U.S. Environmental Protection Agency	NLM_CIP: National Library of Medicine ChemID plus database
EPA_AEGL: Acute Exposure Guideline Levels (U.S. Environmental Protection Agency)	NLM_HSDB: National Library of Medicine Hazardous Substance Data Bank
EPA_FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act Reregistration Eligibility Decision (U.S. Environmental Protection Agency)	NLM_PUBMED: National Library of Medicine PubMed database
	NTP: National Toxicology Program

Aluminum, 3xxx Series Alloys

Safety Data Sheet

According to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

EPA_HPVS: High Production Volume Chemicals (U.S. Environmental Protection Agency)	NZ_CCID: New Zealand Chemical Classification and Information Database
EPA_TRED: Risk Assessment for Tolerance Reassessment Eligibility Decision (U.S. Environmental Protection Agency)	OECD_EHSP: Environment, Health, and Safety Publication (Organisation for Economic Co-operation and Development)
EU_CLH: European Union Harmonised Classification and Labelling Proposal	OECD_SIDS: Screening Information Data Sets (Organisation for Economic Co-operation and Development)
EU_RAR: European Union Risk Assessment Report	WHO: World Health Organization

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)